

Concealed floor standing unit

FNQ-A



Home leave operation

Designed to be concealed in walls

- › Ideal for installation in offices, hotels and residential applications
- › Blends unobtrusively with any interior décor: only the suction and discharge grills are visible
- › Its low height (620 mm) enables the unit to fit perfectly beneath a window
- › Requires very little installation space as the depth is only 200mm
- › High ESP allows flexible installation

FNQ-A + RXS-L/RXS-L3



Indoor unit		FNQ	25A	35A	50A	60A
Casing	Colour		Unpainted			
Dimensions	Unit	HeightxWidthxDpeth	620 / 720x790x200		620 / 720x1,190x200	
Sound power level	Cooling		53		56	
	Heating	High/Nom./Low	33/31/28		36/33/30	
Sound pressure level	Cooling	High/Nom./Low	33/31/28		36/33/30	
	Heating	High/Nom./Low	33/31/28		36/33/30	
Control systems	Infrared remote control		BRC4C65			
	Wired remote control		BRC1D52 / BRC1E52A/B			

EER/COP according to Eurovent 2012, for use outside EU only | Including installation legs


Efficiency data		FNQ + RXS	25A + 25L3	35A + 35L3	50A + 50L	60A + 60L	
Cooling capacity	Nom.	kW	2.6	3.4	5.0	6.0	
Heating capacity	Nom.	kW	3.20	4.00	5.80	7.00	
Power input	Cooling	Nom.	0.69	1.11	1.49	2.24	
	Heating	Nom.	0.80	1.15	1.74	2.25	
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A+				
		Pdesign	2.60	3.40	5.00	6.00	
		SEER	5.63	5.65	5.72	5.51	
	Heating (Average climate)	Annual energy consumption	kWh	162	211	306	381
		Energy efficiency class	A+				
Nominal efficiency	EER	Pdesign	2.80	2.90	4.00	4.60	
		SCOP/A	4.24	4.05	4.09	4.16	
		Annual energy consumption	kWh	925	1,002	1,369	1,548
	COP	EER	3.77	3.06	3.35	2.68	
		COP	4.00	3.48	3.34	3.11	
Annual energy consumption	kWh	345	556	746	1,119		
Energy labeling	Cooling		A	B	A	D	
Directive	Heating		A	B	C	D	

Contains fluorinated greenhouse gases

Outdoor unit		RXS	25L3	35L3	50L	60L
Dimensions	Unit	HeightxWidthxDpeth	550x765x285		735x825x300	
Sound power level	Cooling		59	61	62	
	Heating		59	61	62	
Sound pressure level	Cooling	High/Low/Silent operation	46/-/43	48/-/44	48/44/-	49/46/-
	Heating	High/Low/Silent operation	47/-/44	48/-/45	48/45/-	49/46/-
Operation range	Cooling	Ambient Min.-Max.	-10~-46			
	Heating	Ambient Min.-Max.	-15~-18			
Refrigerant	Type/Charge/GWP	kg/TCO ₂ eq	R-410A/1.0/2.1/2,087.5	R-410A/1.2/2.5/2,087.5	R-410A/1.7/3.5/2,087.5	R-410A/1.5/3.1/2,087.5
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		1~/50/220-230-240	

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

ECPEN17-109

02/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.