



Pair, Twin,
Triple, double
twin
RZQ-C



Inverter



Auto cooling-heating
changeover

Packaged system for commercial applications

- › Re-use of existing R-22 or R-407C technology
- › Guarantees operation in heating mode down to -15°C
- › Standard night quiet mode
- › Maximum piping length up to 100m
- › Maximum installation height difference up to 30m
- › Wide range of connectable indoor units

RZQ-C





RZQ200-250C

	FCQG-F					FFQ-C		FDXS-F(9)		FBQ-D					FHQ-C					FUQ-C			FAQ-C		FDQ-C	FNQ-A	
capacity class	50	60	71	100	125	50	60	50	60	50	60	71	100	125	50	60	71	100	125	71	100	125	71	100	125	50	60
RZQ200C	4	3	3	2		4	3	4	3	4	3	3	2		4	3	3	2		3	2		3	2		4	3
RZQ250C		4			2		4		4		4			4		2			2			2			2		4

Outdoor unit		RZQ		200C					250C									
Dimensions	Unit	HeightxWidthxDepth		mm					1,680x930x765									
Sound power level	Cooling			dBA					78									
	Heating			dBA					78									
Sound pressure level	Nom.			dBA					57									
Operation range	Cooling	Ambient	Min.-Max.	°CDB					-5.0~46.0									
	Heating	Ambient	Min.-Max.	°CWB					-15.0~15.0									
Refrigerant	Type/Charge/GWP			kg/TCO ₂ eq					R-410A/8.3/17.3/2,087.5					R-410A/9.3/19.4/2,087.5				
Power supply	Phase/Frequency/Voltage			Hz/V					3N~/50/380-415									

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-127 04/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.