

# Wall mounted unit

FTXK-AW/S + RXK-A



Comfortable sleeping mode



Vertical auto swing



24 hour timer

Stylish wall mounted unit for low energy consumption and pleasant comfort

- › Stylish, modern casing in white
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time

- › Large operation range (ambient temperature up to 43°C)

# FTXK-AW/S + RXK-A



Indoor unit		FTXK	25AW/S	35AW/S	50AW/S	60AW/S
Casing	Colour		White			
Dimensions	Unit	HeightxWidthxDepth	297x890x210		320x1,172x242	
Sound power level	Cooling/Heating		53/53	54/54	55/55	61/61
Sound pressure level	Cooling	Super high/High/Nom./Low/Silent operation	41/40/34/29/21	42/41/34/30/22	44/40/38/35/32	46/43/41/37/33
	Heating	Super high/High/Nom./Low/Silent operation	41/40/34/29/21	42/41/34/30/22	44/40/38/35/32	46/43/41/37/33

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load


Efficiency data		FTXK + RXK	25AW/S + 25A	35AW/S + 35A	50AW/S + 50A	60AW/S + 60A		
Cooling capacity	Min./Nom./Max.	kW	1.300/2.500 (2/3.000)	1.300/3.500 (2/3.800)	1.630/5.480 (2/6.200)	1.750/6.230 (2/6.500)		
Heating capacity	Min./Nom./Max.	kW	1.300/3.300 (2/4.000)	1.300/3.600 (2/4.750)	1.170/5.620 (2/6.600)	1.200/6.400 (2/8.000)		
Power input	Cooling	Min./Nom./Max.	kW	0.280/0.731 (2/0.990)	0.290/1.075 (2/1.390)	0.290/1.700 (2/2.000)	0.280/1.931 (2/2.000)	
	Heating	Min./Nom./Max.	kW	0.260/0.900 (2/1.100)	0.285/0.957 (2/1.480)	0.260/1.550 (2/2.510)	0.240/1.680 (2/2.000)	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+					
		Pdesign	kW	2.50	3.50	5.48	6.23	
		SEER		5.66	5.86	5.93	6.09	
	Heating (Average climate)	Annual energy consumption	kWh	155	209	324	359	
		Energy label	A+					
		Pdesign	kW	2.40	2.80	3.37	3.80	
Nominal efficiency	EER	COP	Annual energy consumption	kWh	3.42 (1)	3.26 (1)	3.22 (1)	3.23 (1)
					3.67 (1)	3.76 (1)	3.63 (1)	3.81 (1)
	Energy label	Cooling/Heating	A/A					

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Outdoor unit		RXK	25A	35A	50A	60A
Dimensions	Unit	HeightxWidthxDepth	550x658x289		628x855x328	753x855x328
Sound power level	Cooling		58	60	64	65
	Heating		58	60	64	65
Sound pressure level	Cooling	Nom.	45	46	51	
	Heating	Nom.	45	46	51	
Operation range	Cooling	Ambient	Min.-Max.	-10~-46		
	Heating	Ambient	Min.-Max.	-15~-18		
Refrigerant	Type/GWP	R-410A/2,087.5				
	Charge	kg/TCO <sub>Eq</sub>	0.74/1.5	1.00/2.1	1.25/2.6	1.45/3.0
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			

Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPE15-026 07/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.