

Wall mounted unit

FTXLS-K



Guaranteed operation down to **-25°C**



2 area intelligent eye



Whisper quiet



Online controller via app

Discreet modern design for optimal efficiency and comfort thanks to 2 area intelligent eye, even at ambient temperatures **down to -25°C**

- › High quality matt crystal white finish
- › Excellent air flow and air distribution
- › Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- › New remote control design, also in high quality matt white finish to give a perfect match with the indoor unit

- › Online controller (optional): control your indoor from any location with an app, via your local network or internet
- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › Thanks to the unique free hanging coil technology, the defrost cycle is improved, resulting in lower running costs and no ice buildup

FTXLS-K + RXLS-M



Indoor unit		FTXLS	25K	35K
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDpht	mm	
			298x900x215	
Sound power level	Cooling		dBA	
			59	
Sound pressure level	Heating		dBA	
			62	
Control systems	Cooling	High/Nom./Low/Silent operation	dBA	
			45/39/33/21	
	Heating	High/Nom./Low/Silent operation	dBA	
			47/39/33/19	
			ARC466A9	


Efficiency data		FTXLS + RXLS	25K + 25M	35K + 35M
Cooling capacity	Min./Nom./Max.	kW	1.6/2.5/4.4	1.7/3.5/5.0
Heating capacity	Min./Nom./Max.	kW	1.0/4.7/6.6 / 3.98 (1)	1.0/5.4/7.2 / 4.51 (1)
Power input	Cooling	Min./Nom./Max.	kW	
			0.320/0.669/2.330	
	Heating	Min./Nom./Max.	kW	
			0.240/1.100/2.360	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A++	
		Pdesign	2.50	3.50
		SEER	6.62	6.91
	Heating (Average climate)	Energy label	A++	
		Pdesign	3.20	3.80
		SCOP	4.62	4.60
Nominal efficiency	Annual energy consumption		947	1,147
	EER		3.74	3.69
	COP		4.27	4.12
	Annual energy consumption	kWh	334.5	475.5
	Energy label	Cooling/Heating	A/A	

Outdoor unit		RXLS	25M	35M
Dimensions	Unit	HeightxWidthxDpht	mm	
			550x858x330	
Sound power level	Cooling		dBA	
			61	
Sound pressure level	Heating		dBA	
			61	
Operation range	Cooling	High/Low	dBA	
			48/44	
Refrigerant	Heating	High/Low	dBA	
			49/45	
Type/GWP	Cooling	Ambient	Min.-Max. °CDB	
			-10~-46	
Charge	Heating	Ambient	Min.-Max. °CWB	
			-25~-18	
Power supply	Type/GWP		R-410A/2,087.5	
	Charge	kg /TCO ₂ Eq	1.3/2.7	
Phase/Frequency/Voltage		Hz/V	1~/50/220-240	

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load
 (1) Maximum average heating capacity at -15°C

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-031 01/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.