

## Ceiling mounted corner cassette

FXXQ-MA



### 1-way blow unit for corner installation

- › Compact dimensions, can easily be mounted in a narrow ceiling void (only 220mm ceiling space required, 195 with panel spacer, available as accessory)
- › Optimum air flow conditions are created by either downward air discharge or frontal air discharge (via optional grille) or a combination of both


# FXKQ-MA



Indoor unit		FXKQ	25MA	32MA	40MA	63MA	
Cooling capacity	Nom.	kW	2.8	3.6	4.5	7.10	
Heating capacity	Nom.	kW	3.2	4.0	5.0	8.00	
Power input - 50Hz	Cooling	Nom.	0.066		0.076	0.105	
	Heating	Nom.	0.046		0.056	0.085	
Dimensions	Unit	Height	mm				215
		Width	mm			1,110	1,310
		Depth	mm			710	
Weight	Unit	kg	31			34	
Casing	Material	Galvanised steel plate					
Decoration panel	Model	BYK45FJW1				BYK71FJW1	
	Colour	White					
	Dimensions	HeightxWidthxDepth	mm			70x1,240x800	70x1,440x800
	Weight	kg			8.5	9.5	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m <sup>3</sup> /min		11/9	13/10	18/15
Air filter	Type	Resin net with mold resistance					
Sound power level	Cooling	Nom.	dBA			-	
Sound pressure level	Cooling	High/Low	dBA		38.0/33.0	40.0/34.0	42.0/37.0
			Refrigerant Type/ GWP				
Piping connections	Liquid	OD	mm			6.35	9.52
		Gas	mm			12.7	15.9
	Drain	VP25 (O.D. 32 / I.D. 25)					
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/60/220-240/220			
Current - 50Hz	Maximum fuse amps (MFA)	A		15			
Control systems	Infrared remote control		BRC4C61				
	Simplified wired remote control for hotel applications		-				
	Wired remote control		BRC1D52 / BRC1E52A/B				

Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-241

02/15



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.