

Concealed floor standing unit

FXNQ-A



Multi tenant

Designed to be concealed in walls

- › Discretely concealed in the wall: only the suction and discharge grilles are visible
- › Requires very little installation space as the depth is only 200mm
- › Its low height (620 mm) enables the unit to fit perfectly beneath a window


FXNQ-A



Indoor unit		FXNQ	20A	25A	32A	40A	50A	63A
Cooling capacity	Nom.	kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Nom.	kW	2.5	3.2	4.0	5.0	6.3	8.00
Power input - 50Hz	Cooling	Nom.	0.071			0.078	0.099	0.110
	Heating	Nom.	0.068			0.075	0.096	0.107
Dimensions	Unit	Height	mm					
		Width	mm			mm		
		Depth	mm					
Weight	Unit	kg	23.5			27.5		32
Casing	Colour	Unpainted						
	Material	Galvanised steel plate						
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min			10.5/8.5	12.5/10.0	16.5/13.0
	Heating	High/Low	m ³ /min			8.0/6.4	10.5/8.5	12.5/10.0
Fan-External static pressure	High/Nom.	Pa	41/10		42/10	52/15	59/15	55/15
Air filter	Type	Resin net with mold resistance						
Sound power level	Cooling	High/Nom.	dBA			51/-	52/-	53/-
Sound pressure level	Cooling	High/Nom./Low	dBA			30/28.5/27	32/30/28	33/31/29
	Heating	High/Nom./Low	dBA			30/28.5/27	32/30/28	33/31/29
Refrigerant	Type	R-410A						
	GWP	2,087.5						
Piping connections	Liquid	OD	mm			6.35		9.52
	Gas	OD	mm			12.7		15.9
	Drain	VP20 (I.D. 20/O.D. 26)						
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)	A	16					
Control systems	Infrared remote control	BRC4C65						
	Wired remote control	BRC1E53A / BRC1E53B / BRC1E53C / BRC1D52						
	Simplified wired remote control for hotel applications	BRC2E52C (heat recovery type) / BRC3E52C (heat pump type)						

(1) Including installation legs | Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-262

12/16



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.